

Chrysler Corporation Sarlink® Approvals

Specification Number	Title	Sarlink® Grade Approved
MS-AR-100 AGN (Supersedes MS-AR20A)	TPR – Fully Cured EPDM in a Polyolefin Base	4155N/B
MS-AR-100 BGN (Supersedes MS-AR20B)	TPR – Fully Cured EPDM in a Polyolefin Base	4165N/B
MS-AR-100 CGN (Supersedes MS-AR20C)	TPR – Fully Cured EPDM in a Polyolefin Base	4175N/B
MS-AR-100 DGN (Supersedes MS-AR20D)	TPR – Fully Cured EPDM in a Polyolefin Base	4180N/B
MS-AR-100 EGN (Supersedes MS-AR20E)	TPR – Fully Cured EPDM in a Polyolefin Base	4190N/B
MS-AR-100 AGV (Supersedes MS-AR23A)	TPR – Fully Cured EPDM in a Polyolefin Base - UV Stabilized	5755B4
MS-AR-100 BGV (Supersedes MS-AR23B)	TPR – Fully Cured EPDM in a Polyolefin Base - UV Stabilized	5765B4
MS-AR-100 CGV (Supersedes MS-AR23C)	TPR – Fully Cured EPDM in a Polyolefin Base - UV Stabilized	5775B4
MS-AR-100 EGV (Supersedes MS-AR23E)	TPR – Fully Cured EPDM in a Polyolefin Base - UV Stabilized	5790B4
MS-AR-100 AMV (Supersedes MS-AR24A)	TPR – Fully Cured EPDM in a Polyolefin Base - High Flow – UV Stabilized	4750 B42
MS-AR-100 BMV (Supersedes MS-AR24B)	TPR – Fully Cured EPDM in a Polyolefin Base - High Flow – UV Stabilized	4765 B40
MS-AR-100 CMV (Supersedes MS-AR24C)	TPR – Fully Cured EPDM in a Polyolefin Base - High Flow – UV Stabilized	4775 B40
MS-AR26F	TPR – Fully Cured EPDM in a Polyolefin Base – Colorable, UV Stabilized, Interior	3160N-43 3160B-43
MS-AR-100 FGN (Supersedes MS-AR30A)	TPR – Fully Cured EPDM in a Polyolefin Base	4139DN 4139DB
MS-AR-100 GGN (Supersedes MS-AR30B)	TPR – Fully Cured EPDM in a Polyolefin Base	4149DN 4149DB
MS-AR80A	TPE – Partially Cured EPDM in a Polyolefin Matrix	3150N / 3150B
MS-AR80B	TPE – Partially Cured EPDM in a Polyolefin Matrix	3160N / 3160B
MS-AR80C	TPE – Partially Cured EPDM in a Polyolefin Matrix	3170N / 3170B
MS-AR80D	TPE – Partially Cured EPDM in a Polyolefin Matrix	3180N / 3180B
MS-AR80E	TPE – Partially Cured EPDM in a Polyolefin Matrix	3190N / 3190B
MS-AR80Ev	TPE – Partially Cured EPDM in a Polyolefin Matrix	3190N / 3190B

Note: Chrysler is now relying heavily on ASTM line-call outs. There fore any needed material which does not fall under these approvals can be positioned by using a line-call out. Specific color approvals will still be needed for color critical applications.

Ford Motor Company Sarlink® Approvals

Specification Number	Title	Sarlink® Grade Approved
WSD-M2D378-A1	TPE (TEO) Polyolefin, EPDM, EC, M. Heat Res. 60A	4155N/B
WSS-M2D378-B1	TPE (TEO) Polyolefin, EPDM, Exterior Weatherable, 60A	5755B4
WSD-M2D379-A1	TPE (TEO) Polyolefin, EPDM, EC, M. Heat Res. 68A	4165N/B
WSS-M2D379-B1	TPE (TEO) Polyolefin, EPDM, Exterior Weatherable, 68A	5765B4
WSD-M2D380-A1	TPE (TEO) Polyolefin, EPDM, EC, M. Heat Res. 76A	4175N/B
WSS-M2D380-B1	TPE (TEO) Polyolefin, EPDM, Exterior Weatherable, 73A	5775B4
WSD-M2D381-A1	TPE (TEO) Polyolefin, EPDM, EC, M. Heat Res. 82A	4180N/B
WSD-M2D382-A1	TPE (TEO) Polyolefin, EPDM, EC, M. Heat Res. 89A	4190N/B
WSD-M2D441-A	TPE (TEO) Polyolefin, EPDM12M Rubber Modified	4139DN/B
WSK-M4D712-A1	TPE (TEO) Polyolefin, EPDM Rubber Mod. 50D	3145DN/B
Ford Endorsed – ASTM Callout		5790B4

- Ford using ASTM line call outs from this point forward except where it involves safety and colorable applications. In these cases material and color approvals are still needed.
- Ford is using performance specifications for Dynamic and Static sealing applications. Dynamic Specification – WSS-M9P9-A / Static Specification – WSS-M9P10-A

General Motors Corporation Sarlink® Approvals

Specification Number	Title	Sarlink® Grade Approved
GMN.3901.E/P.092	TPE, Injection Grade, Shore A65, Interior/Exterior Color/Weatherable	4765B40
GMP.E/P.001	TPE, Polyolefinic Underhood & Int. Applications Shore A 55	4155N/B
GMP.E/P.002	Thermoplastic Polyolefin Elastomer - HS, Alloy, Shore A64	4165N/B
GMP.E/P.003	Thermoplastic Polyolefin Elastomer - HS, Alloy, Shore A73	4175N/B
GMP.E/P.004	Thermoplastic Polyolefin Elastomer - HS, Alloy, Shore A80	4180N/B
GMP.E/P.005	Thermoplastic Polyolefin Elastomer - HS, Alloy, Shore A87	4190N/B
GMP.E/P.006	Thermoplastic Polyolefin Elastomer - HS, Alloy, Shore D40	4139DN/B
GMP.E/P.007	Thermoplastic Polyolefin Elastomer - HS, Alloy, Shore D50	4149D
GMP.E/P.029	Thermoplastic Elastomers – Polyolefinic, Interior/Exterior, Shore A67	5765B4 Leominster / Genk Sites / Texas
GMP.E/P.037	Thermoplastic Elastomers Polyolefinic, Shore A87, Interior/Exterior	5790B4
GMP.E/P.057	Thermoplastic Elastomer – Polyolefinic, Interior/Exterior, Shore A73	5775B4
GMP.E/P.078	Thermoplastic Elastomer Polyolefinic, Shore A50, Interior/Exterior and Underhood Applications	4750B42
GMP.E/P.097 or GMN 3927	Thermoplastic Elastomer Polyolefinic, Shore A35, Interior/Exterior, Injection or Extrusion Grade	5735B4
GMP.E/P.109	Thermoplastic Elastomer, Shore A56 , Exterior, Extrusion Grade	5755B4
GMP.E/P.016	Thermoplastic Elastomer – Polyolefinic, Interior/Exterior, Shore D50	5750DB4
GMW 15812P Type 4E	Thermoplastic Elastomer, Shore 55A, UV, Extrusion Grade	5755B4
GMW 15812P Type 5M	Thermoplastic Elastomer, Shore 65A , UV, Molding Grade	4765B40
GMW 15812P Type 5E	Thermoplastic Elastomer, Shore 65A , UV, Extrusion Grade	5765B4 (Leominster, MA and Genk, Belgium)
GMW 15812P Type 6M	Thermoplastic Elastomer , Shore 75A, UV, Molding Grade	4775B40
GMW 15812P Type 6E	Thermoplastic Elastomer, Shore 75A , UV, Extrusion Grade	5775B4
GMW 15812P Type 8M	Thermoplastic Elastomer, Shore 85A, UV, Molding Grade	4785B40
GMW 15812 Type 8E	Thermoplastic Elastomer, Shore 85A, UV, Extrusion Grade	5790B4
GMW 15812 Type 10E	Thermoplastic Elastomer, Shore 50D UV, Extrusion Grade	5750DB4
GM Sarlink Color Approvals	848 Black, Gloss GLG	4765B40, 4750B42, 5755B4, 5765B4, and 5775B4

GM-Opel QK003500 Listed Sarlink® Grades

Specification Number	Certification Statement Available	Sarlink® Grade Approved
QK 3511	GMW 3013	3140
QK 3513		3150N/B
QK 3513		4155
QK 3513 L		4755B-42
QK 3521		3160N/B
QK 3521		4165
QK 3521		4165B-07
QK 3521 L		5765B-04
QK 3521		6165N-03
QK 3522 L		4775B-40
QK 3523	GMW 3013	3170B
QK 3523		4175
QK 3523 L		4775B-42
QK 3523 L		5775B-04
QK 3525		3180
QK 3525 L		3780B
QK 3525		4180
QK 3525		3190
QK 3526		4190N/B
QK 3531		4139DN/B
QK 3531	GMW 3013	3939D-01
QK 3531	GMW 3013	K 156B
QK 3532		3139D
QK 3533		3145DN/B

Delphi Corporation Sarlink® Approvals

Specification Number	Title	Sarlink® Grade Approved
DX300100 Delphi Interior Systems	Thermoplastic Polyolefin Elastomer – Heat Stabilized, Alloy, Shore A73	4175
7845728 Delphi Saginaw Steering Systems	Spec, Material 40D Olefinic Thermoplastic Elastomer	4139DB
MX300100	Thermoplastic Polyolefin Elastomer – UV Stabilized, Shore A75	5775B4

VW-Audi-Seat-Skoda (VAG) Sarlink® Approvals

VAG (VW-Audi-Seat-Skoda)	Specification
Sarlink 3140B	VW 501 23
Sarlink 3140N	VW 501 23
Sarlink 3140	VW 501 79
Sarlink 3140	VW 501 80
Sarlink 3150B	VW 501 23
Sarlink 3150	VW 501 79
Sarlink 3150	VW 501 80
Sarlink 3160B	VW 501 23
Sarlink 3150N	VW 501 23
Sarlink 3170B	VW 501 23
Sarlink 3170	VW 501 80
Sarlink 3180B	VW 501 23
Sarlink 3180	VW 501 79 (Audi)
Sarlink 3180	VW 501 80
Sarlink 3180B	TL 526 22
Sarlink 3190B	VW 501 23
Sarlink 3139DB	VW 501 23
Sarlink 3139DB	VW 501 80
Sarlink 3139D-01	VW 501 23
Sarlink 3939DB-01	VW TL1010
Sarlink 3145DB	VW 501 23
Sarlink 4155B	VW 501 23
Sarlink 4165B	VW 501 23
Sarlink 4175B	VW 501 23
Sarlink 4180B	VW 501 23
Sarlink 4190B	VW 501 23
Sarlink 4755B-42	VW 501 23
Sarlink 4765B-40	VW 501 23
Sarlink 4765B-42	VW 501 23
Sarlink 4775B-40	VW 501 23
Sarlink 4775B-42	VW 501 23
Sarlink 5755B4	VW 501 23
Sarlink 5765B4	VW 501 23
Sarlink 5765B4	TL526 41-C
Sarlink 5775B4	VW 501 23
Sarlink 6145N	VW 501 23
Sarlink 6165-03N	VW 501 23
Sarlink X6165N-03	VW 501 80
Sarlink K156B	VW TL 526 22-MD01
Sarlink TPE65	VW 501 23

Peugeot-Citroën PSA Sarlink® Approvals

RMA, SPA or FTM number	Grade-color Reference	Validations B620300 Norm
X62 3450	Sarlink 3140B Sarlink 3150B Sarlink 3160B-FXT Sarlink 3170B-FXT	16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J4-J5 K3-K4? L207E P207E M1 O1 N1 Q3 Ro To8 Z2 16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J5-J6 K3-K4? L207E P207E M1 O1 N1 Q3 R1 To81 Z2
X62 3458	Sarlink 3139DB-FXT Sarlink 3939DB-FXT Sarlink 3145DB-FXT	B620300 - 16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J4-J5 K3-K4? L207E P207E M1 O1 N1 Q3 Ro To8 Z2 16 211M >35 411 43 53 A1 Bo C1 D1 E3 F10-F2 J7-J8 K4 M2 O1 N1 Q3 R2 To81 Z9 16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J4-J5 K3-K4? L207E P207E M1 O1 N1 Q3 Ro To8 Z2
PP—0012	Sarlink 5765B4-FXT	19? 211M 35 411 40 53 A1 Bo C1 D1 E1 F10-F2 G1 I1 J3-J4 K3-K4? L207E P207E Mo O1? N1 Q2 Ro Z1
PP—0013	Sarlink 5765B4-FXT Sarlink 5775B4-FXT	19 211M 35 411 43 53 A1 Bo C1 D1 F10-F2 G1 I1 J4-J5 K3-K4? L207E P207E M1 O1 N1 Q3 R1 To81 Z2 19 211M 35 411 43 53 A1 Bo C1 D1 F10-F2 G1 I1 J5-J6 K3-K4? L207E P207E M1 O1 N1 Q3 R1 To8 Z2
X62 3458, PP—07	Sarlink 3139DB-FXT Sarlink K165B-FXT	16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J8 K3-K4? M2 O1 N1 Q3 R3 To81 Z10 19 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 G1 I1 J8 K3-K4? M2 O1 N1 R1 Z9
X623492, PP—08	Sarlink 3190B-FXT Sarlink 4139DB-FXT Sarlink 3780B-FXT Sarlink 3790B40-FX Sarlink 3380B-FXT Sarlink 3380B-FXT Sarlink 4755B42-FXT Sarlink 4755B42-FXT Sarlink 4775B42-FXT Sarlink 4775B42-FX	16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J8 K3-K4? M2 O1 N1 Q3 R3 To81 Z10 19 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 G1 I1 J5-J6 K3-K4? L207E P207E M1 O1 N1 Q3 Ro Z2 16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J8 K3-K4? M2 O1 N1 Q3 R3 To81 Z10 17 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 G1 I1 J7-J8 K3-K4? M1 O1 N1 Q3 R2 To7 Z9 16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J8 K3-K4? M2 O1 N1 Q3 R3 To81 Z10 16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J4-J5 K3-K4? L207E P207E M1 O1 N1 Q3 Ro To8 Z2 19 211M 35 411 43 53 A1 Bo C1 D1 F10-F2 G1 I1 J4-J5 K3-K4? L207E P207E M1 O1 N1 Q3 R1 To81 Z2 19? 211M 35 411 40 53 A1 Bo C1 D1 E1 F10-F2 G1 I1 J3-J4 K3-K4? L207E P207E Mo O1? N1 Q2 Ro Z1 16 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 J8 K3-K4? M2 O1 N1 Q3 R3 To81 Z10 19 211M 35 411 40 53 A1 Bo C1 D1 F10-F2 G1 I1 J8 K3-K4? M2 O1 N1 R1 Z9

Daimler Sarlink® Approvals

Daimler (Mercedes)	Specification
Sarlink 3150B	DBL 5562.30
Sarlink 3160B	DBL 5562.30
Sarlink 3170B	DBL 5562.30
Sarlink 3180B	DBL 5562.30
Sarlink 4150B-42	MS-AR24
Sarlink 4155B	DBL 5562.30
Sarlink 4755B-42	DBL 5562.30
Sarlink 4765B-42	DBL 5562.30
Sarlink 4775B-40	DBL 5562.30
Sarlink 4775B-42	DBL 5562.30
Sarlink 5725B4	DBL 5562.?? (25 Shore A)
Sarlink 5745B4	DBL 5562.30
Sarlink 5755B4	DBL 5562.30
Sarlink 5765B4	DBL 5562.30
Sarlink 5775B4	DBL 5562.30
Sarlink 7765B4	DBL 5562.30
Sarlink K X935DB	DBL 5562.20

Sarlink® Approvals at Japanese Automotive OEM's

The Japan OEM's (Toyota, Honda, and Nissan) do not have material specifications similar to the Big 3 in Detroit. The Japan OEM's will specify a part performance specification that will typically include a table showing properties of a TPO or TPV. Some material specifications do exist, and list general properties. In all cases, the Tier 1 supplier

has the option to test materials to the Part Performance and Material specifications.

For example, Toyota Engineering Standard TSM1707G covers the materials and product performances for Door Glass Weatherstrip. Table 2 of this specification summarizes the material performance. Sarlink is considered a Class 7 material (material code TSM1707G-7), and identified as PP + EPDM.

Nissan Engineering Standard M7082 "Rubber Materials for Automotive Weatherstrip" is used to specify rubber materials and TPV is specified with the general designation of WG (PP/EPDM).

Below is a list of Sarlink® grades that are currently commercial at the Japanese Automotive OEM's.

OEM	Application	Sarlink® Grade
Toyota	Air Duct	4175B-05
	Boots	4165B
Honda	Cowl Top, Hood Hinge	4775B40, 4765B40
	Mats, Bin Liners, knobs	3160B
		3150B
		4775B40
		Various custom colors via Trexlink™
	Air Duct/Hose	4155B
	Strake (stone guard)	5790B4
	Fuel Cell Gasket	3150B
	Steering Boot	4190B
Nissan	Inner Belt Seal	5755B4, TM80
	Inner Belt Seal	5765B4

Revised: December 20, 2010



Corporate Headquarters

Telephone +1.866.438.8737 (all TPE enquiries)
Telephone +1.800.556.3864 or
+1.401.725.8000 (Teknor Apex Company)

Americas (all Sarlink® enquiries)

Telephone: +1.978.534.1010
Toll Free (USA only): 800.524.0120

Europe

Telephone: +31.46.70.20.950

Asia

Telephone: +86.(21) 5010.8083

Japan

Telephone: +81.352095151

About Teknor Apex TPE

The Thermoplastic Elastomer Division of Teknor Apex Company (TA TPE) is the most diversified manufacturer of TPEs, offering seven broad product families based on generically distinct chemistries and operating plants in the US, Europe, and Asia. The processes used by TA TPE produce compounds that exhibit outstanding rubber-like properties with particular characteristics while being processable at high rates like any other thermoplastic, as well as being recyclable. Visit www.teknorapex.com/tpe to see the TPE product families. Headquartered in Pawtucket, Rhode Island, US, the Division is an international supplier to the appliance, automotive, construction, medical-device, wire and cable, and other consumer and industrial product industries. Other plastics businesses of Teknor Apex include the Bioplastics, Nylon, Specialty Compounding, and Vinyl Divisions and Teknor Color Company. Visit www.teknorapex.com.

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchaser assumes all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described. For detailed Product Stewardship information, please contact us. Any product of TA TPE, including product names, shall not be used or tested in any medical or food contact application without the prior written acknowledgement of TA TPE as to the intended use. Please note that some products may not be available in one or more countries.

www.teknorapex.com/sarlink